




TALIA 901 X

Cod. 02029380

EAN 8422248378086



GENERAL INFORMATION

EAN/UPC	8422248378086
Subfamily	Box

Product sheet according to directives EU65/2014 - EN61591, EN60704-2-13, EN50564

AEC (Annual energy consumption) (kWh/year)	306
FDE (fluid dynamic efficiency)	98
LE (light efficiency) (lux/W)	44
GFE (grease filtering efficiency)	653
Airflow in normal mode MIN (m3/h)	2197
Airflow in normal mode MAX (m3/h)	292
Acoustic power in normal mode MIN (dB)	60
Acoustic power in normal mode MAX (dB)	67
Po (energy consumption in off mode) (W)	0

Integration directive EU 66/2014

f (time increase factor)	16
EEL (Energy Efficiency Index)	699
QBEP (maximum efficiency at air flow point) (m3/h)	1365
PBEP (maximum efficiency at pressure point) (Pa)	129
WBEP (power consumption at maximum efficiency) (W)	499
WL (nominal power lighting system) (W)	2
EMIDDLE (Average illuminance on the cooking surface) (lux)	44

External Dimensions

Width (mm)	900
Depth (mm)	450
Maximum total height (mm)	830
Minimum total height (mm)	450

Characteristics

Motor quantity	1
Motor model	AC 65
Maximum pressure (Pa)	252
Free out airflow (m3/h)	300
Filter technology	Aluminium mesh
Control technology	Mechanical push button
Booster	-
Power levels	3
Timer	-
Filter saturation indicator	-
Charcoal filter replacement indicator	-
Dimmer function	-
Connectivity	-
Remote control	-
Display	-

Lighting

Light model	CSLED
Ray technology	LED

Installation

Minimum distance to electric plate (mm)	5
Recirculation option	√
Charcoal filter	-
Back draught shutter	-
Inner shield	-

Electric connection

Nominal voltage (V)	220-240
Nominal frequency (Hz)	50
Plug type	No plug

Accessories

Upper decorative duct extension	No
White decorative duct	No
Black decorative duct	No
Island tube booster	No

Back draught shutter	No
MAX PRO Metal filter	No
Activated charcoal filter	No
Noiseless flexible duct	No
Recirculation kit	Optional